



Material number	Model	Rated voltage	Specific ation	Approximate outer diameter of the cable (mm)	Approximate weight (kg/km)	Conductor resistance (Ω /km)
62930. IEC131.0101.5	62930 IEC 131	1.5Kv DC	1*1.5	4.6	36	13.70
62930. IEC131.0102.5	62930 IEC 131	1.5Kv DC	1*2.5	5.0	46	8.21
62930. IEC131.01004	62930 IEC 131	1.5Kv DC	1*4	5.6	62	5.09
62930. IEC131.01006	62930 IEC 131	1.5Kv DC	1*6	6.1	82	3.39
62930. IEC131.01010	62930 IEC 131	1.5Kv DC	1*10	7.1	125	1.95
62930. IEC131.01016	62930 IEC 131	1.5Kv DC	1*16	8.5	190	1.24
62930. IEC131.01025	62930 IEC 131	1.5Kv DC	1*25	10.4	285	0.795
62930. IEC131.01035	62930 IEC 131	1.5Kv DC	1*35	11.5	385	0.565
62930. IEC131.01050	62930 IEC 131	1.5Kv DC	1*50	13.7	540	0.393
62930. IEC131.01070	62930 IEC 131	1.5Kv DC	1*70	15.8	740	0.277
62930. IEC131.01095	62930 IEC 131	1.5Kv DC	1*95	17.3	965	0.21
62930. IEC131.01120	62930 IEC 131	1.5Kv DC	1*120	19.1	1210	0.164
62930. IEC131.01150	62930 IEC 131	1.5Kv DC	1*150	21.4	1495	0.132
62930. IEC131.01185	62930 IEC 131	1.5Kv DC	1*185	24.9	1885	0.108
62930. IEC131.01240	62930 IEC 131	1.5Kv DC	1*240	27.3	2395	0.0817