



频率 FREQ	插入损耗 INSERTION LOSS		近端传音衰减 NEXT		衰减串扰比 ACR	综合近端串扰 PS-NEXT		综合衰减串扰比 PS-ACR	等电平远端串音衰 减 ELFEXT	等电平远端串音衰 减功率和 PS-ELFEXT	回波损耗 RL
(MHz)	(dB/100m)		(dB/100m)		(dB/100m)	(dB/100m)		(dB/100m)	(dB/100m)	(dB/100m)	(dB)
	avg 1.6	max 1.8	avg 82	min 72.0	min 70.2	avg 75	min 70.0	min 68.2	min	min	min
0.772									-	-	-
1	1.8	2	80	70.3	68.3	73	68.3	66.3	67.8	64.8	20
4	3.8	4.1	70	61.3	57.2	63	59.3	55.2	55.8	52.8	23
8	5.4	5.8	66	56.8	51	59	54.8	49	49.7	46.7	24.5
10	6	6.5	64	55.3	48.8	58	53.3	46.8	47.8	44.8	25
16	7.6	8.2	62	52.2	44	56	50.2	42	43.7	40.7	25
20	8.6	9.3	60	50.8	41.5	54	48.8	39.5	41.8	38.8	25
25	9.7	10.4	59	49.3	38.9	52	47.3	36.9	39.8	36.8	24.3
31.25	10.9	11.7	58	47.9	36.2	51	45.9	34.2	37.9	34.9	23.6
62.5	15.8	17	54	43.4	26.4	47	41.4	24.4	31.9	28.9	21.5
100	20.5	22	50	40.3	18.3	43	38.3	16.3	27.8	24.8	20.1
155	26.2	28.1	48	37.4	9.4	41	35.4	7.4	24	21	18.8
200	30.2	32.4	46	35.8	3.4	40	33.8	1.4	21.8	18.8	18
250	34.8	36.9	45	34.3	-	38	32.3	-	19.8	16.8	17.3
300	38.5	41	44	33.1	-	37	31.1	-	18.3	15.3	16.8
350	42	44.9	43	32.1	-	36	30.1	-	16.9	13.9	16.3
400	45.2	48.5	42	31.3	-	35	29.3	-	15.8	12.8	15.9